



CODE No.	CONTACT	A	B	C	D	E	F	G
CL537-0028-7-86	20	7.2	4.5	5.3	5.7	6.6	5.3	8.1
CL537-0030-9-86	30	9.7	7.0	7.8	8.2	9.1	7.8	10.6
CL537-0031-1-86	36	11.2	8.5	9.3	9.7	10.6	9.3	12.1
CL537-0032-4-86	40	12.2	9.5	10.3	10.7	11.6	10.3	13.1
CL537-0034-0-86	50	14.7	12.0	12.8	13.2	14.1	12.8	15.6
CL537-0036-5-86	60	17.2	14.5	15.3	15.7	16.6	15.3	18.1

2			PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.2#m min LEAD AREA:GOLD PLATED 0.015#m MIN OTHERS(UNDER PLATING):NICKEL PLATED 2#m min	7	PS	CLEAR (REINFORCEMENT COLLAR)				
					6	PS	BLACK (PLASTIC REEL)				
					5	POLYESTER	CLEAR (COVER TAPE)				
					4	PS	CLEAR (EMBOSSD CARRIER TAPE)				
1			POLYAMIDE	UL94V-0, NATURAL (BEIGE)	3	BRASS	TIN PLATED 2#m MIN (UNDER PLATING):NICKEL 1#m MIN				
NO.		MATERIAL		FINISH , REMARKS		NO.	MATERIAL		FINISH , REMARKS		
UNITS mm				SCALE 5 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-H-00001707		DESIGNED SH. HOSODA	CHECKED TS. MIYAZAKI	DATE 16.06.10
HIROSE ELECTRIC CO., LTD.				APPROVED : KH. IKEDA		12.11.06	DRAWING NO. EDC3-163509-77				
				CHECKED : YH. MICHIDA		12.11.06	PART NO. DF12(3.5)-*DP-0.5V(86)				
				DESIGNED : YN. SAKAMOTO		12.11.06	CODE NO. CL537				
				DRAWN : YN. SAKAMOTO		12.11.06					

