



a vital part of your world

Find Answers:

Thursday, 17 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Multimate Contacts

↳ Multimate

AMP 66107-4 Active

Directive 2002/95/EC Compliant

RoHS Compliant

(Corporate P/N: 66107-4)

[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ➤ General Info ➤ Sales Info ➤ Assembly Subcontractors 	<ul style="list-style-type: none"> ➤ Pricing & Availability 	<ul style="list-style-type: none"> ➤ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Processes:	Not relevant for lead free process
Pin/Socket:	Pin
High Current:	No
Contact Mating Area Plating:	Gold (30) over Nickel (50)
Wire Range (mm [AWG]):	0.12-0.20 ² [26-24]
Insulation Diameter (mm [in]):	0.89 – 1.40 [0.035 – 0.055]
Contact Material:	Brass
Termination End Plating:	Gold Flash

Other Properties:

Pin Diameter (mm [in]):	1.57 [0.062]
Wire/Cable Type:	Discrete Wire
Test Current (Amps.):	13.0
Spring Material:	Stainless Steel
Grade:	Commercial
Used With:	G Series Connectors, CPC Connectors, M Series Connectors

Product Type:	Type III+
Contact Size:	16
Contact Type:	Signal
Terminate To:	Wire
Insulation Support:	Yes
Wire Termination Type:	Crimp
Packaging Method:	Loose Piece

Comment:

Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [.125]. Insertion Tool No. 91002-1 (for Insulation Dia. 1.78 [.070] or less), No. 200893-2 (for Insulation Dia. .090 [2.29] max.) Extraction Tool No. 305183. PRO-CRIMPER II # 58495-1 Hand Tool for field repair use only.

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]