

	TYPE PRODUCT SPECIFICATION	NUMBER GS-12-309	
	TITLE HDMI CONNECTOR PLUG & RECEPTACLE	PAGE 1 of 10	REVISION B
AUTHORIZED BY Leif Shen		DATE 28/10/04	
CLASSIFICATION RELEASED			

1 OBJECTIVE

This specification defines the performance requirements for HDMI connector.

2.0 GENERAL

This document is composed of the following sections

<u>PARAGRAPHS</u>	<u>TITLE</u>
1.0	OBJECTIVE
2.0	GENERAL
3.0	MATERIAL
4.0	ELECTRICAL CHARACTERISTICS
5.0	MECHANICAL CHARACTERISTICS
6.0	ENVIRONMENTAL PERFORMANCE
7.0	RECOMMENDED TEMPERATURE PROFILE
8.0	TEST SEQUENCE

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

Form E-3005
Rev A 02/12/01
V20603

GS-01-001

	TYPE PRODUCT SPECIFICATION	NUMBER GS-12-309	
	TITLE HDMI CONNECTOR PLUG & RECEPTACLE	PAGE 2 of 10	REVISION B
AUTHORIZED BY Leif Shen		DATE 28/10/04	
CLASSIFICATION RELEASED			

3.0 MATERIAL

The material for each component shall be as specified herein, or equivalent.

3.1_Housing: High temperature grass filled resin UL94-V0, color black.

The housing will withdraw exposure to 250 °C peak temperature for 3-6 seconds in a IR reflow oven.

3.2 Contact : copper alloy

3.3 Shell : Copper alloy

3.4 Finish

Contact area: 30u" Au or 15u" GXT under plated 1,27 microns Ni

Solder area: 1.27 microns Sn under plated 1.27 microns Ni.

Shell: 2.54 microns Ni.

4.0 ELECTRICAL CHARACTERISTICS

4.1 Contact Resistance

<Test Condition>

Mated connectors,

Contact : measure by dry circuit, 20 mV maximum, 10mA.

Shell : measured by open circuit, 5 V maximum ,100mA.

(ANSI/EIA-364-06A-83)

<Requirement>

Contact : 30 mΩ maximum.

Shell : 50 mΩ maximum.

4.2 Dielectric Strength

<Test Condition>

Unmated connectors, apply 500 Volts AC (RMS.) between adjacent terminal or ground.

(ANSI/EIA 364-20, Method 301)

Mated connector, apply 300 Volts AC (RMS.) between adjacent terminal and ground.

<Requirement>

No Breakdown

4.3 Insulation Resistance

<Test Condition 1>

Unmated connectors, apply 500 Volts DC between adjacent terminal or ground.

(ANSI/EIA 364-21, Method 302)

<Requirement 1>

100 MΩ minimum (unmated)

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

Form E-3005
Rev A 02/12/01
V20603

GS-01-001

	TYPE PRODUCT SPECIFICATION	NUMBER GS-12-309	
	TITLE HDMI CONNECTOR PLUG & RECEPTACLE	PAGE 3 of 10	REVISION B
AUTHORIZED BY Leif Shen		DATE 28/10/04	
CLASSIFICATION RELEASED			

<Test Condition 2>

Mated connectors, apply 150 Volts DC between adjacent terminal or ground.

<Requirement 2>

10 MΩ minimum (mated)

4.4 Contact Current Rating

<Test Condition>

55 °C, maximum ambient

85 °C, maximum temperature change

(ANSI/EIA-364-70, TP-70)

<Requirement>

0.5 A minimum

4.5 Applied Voltage Rating

<Test Condition>

40 Volts AC (RMS.) continuous maximum, on any signal pin with respect to the shield.

<Requirement>

No Breakdown

4.6 Electrostatic Discharge

<Test Condition>

Test unmated each connector from 1 kV to 8 kV in 1kV steps using 8mm ball probe.

(IEC-801-2)

<Requirement>

No evidence of Discharge to contact at 8 kV

4.7 TMDS Signals Time Domain Impedance

<Test Condition>

Rise time ≤ 200 p sec (10%-90%).

Signal to ground pin ratio per HDMI designation.

Differential Measurement Specimen Environment Impedance = 100 ohms differential

Source-side receptacle connector mounted on a Controlled impedance PCB fixture.

(ANSI/EIA-364-108 Draft Proposal)

<Requirement>

Connector Area : 100 Ω±15%

Transition Area : 100 Ω±15%

Cable Area : 100 Ω±10%

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

Form E-3005
Rev A 02/12/01
V20603

GS-01-001

	TYPE PRODUCT SPECIFICATION	NUMBER GS-12-309	
	TITLE HDMI CONNECTOR PLUG & RECEPTACLE	PAGE 4 of 10	REVISION B
AUTHORIZED BY Leif Shen		DATE 28/10/04	
CLASSIFICATION RELEASED			

4.8 TMDS Signals Time Domain Cross talk FEXT

<Test Condition>

Rise time ≤ 200 psec (10%-90%).
 Signal to ground pin ratio per HDMI designation.
 Differential Measurement Specimen Environment Impedance = 100 ohms differential.
 Source-side receptacle connector mounted on a controlled impedance PCB fixture.
 Driven pair and victim pair.
 (ANSI/EIA-364-90 Draft Proposal)

<Requirement>

5 % maximum

5.0 MECHANICAL CHARACTERISTICS

5.1 Vibration

<Test Condition>

Amplitude : 1.52mm P-P or 147m/s² {15G}
 Sweep time: 50-2000-50Hz in 20 minutes.
 Duration : 12 times in each (total of 36 Times) X, Y, Z axes.
 Electrical load : DC100mA current shall be flowed during the test.
 (ANSI/EIA-364-28 Condition III Method 5A)

<Requirement>

Appearance : No Damage
 Contact Resistance :
 Contact : Change from initial value: 30 m Ω maximum.
 Shell Part : Change from initial value: 50 m Ω maximum.
 Discontinuity : 1 μ sec maximum.

5.2 Shock

<Test Condition>

Pulse width: 11 m sec.,
 Waveform : half sine,
 490m/s² {50G}, 3 strokes in each X.Y.Z. axes
 (ANSI/EIA-364-27, Condition A)

<Requirement>

Appearance : No Damage
 Contact Resistance :
 Contact : Change from initial value: 30 m Ω maximum.
 Shell : Change from initial value: 50 m Ω maximum.
 Discontinuity : 1 μ sec maximum.

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

	TYPE	PRODUCT SPECIFICATION		NUMBER	GS-12-309		
	TITLE			PAGE	6 of 10	REVISION	B
HDMI CONNECTOR PLUG & RECEPTACLE			AUTHORIZED BY	Leif Shen		DATE	28/10/04
			CLASSIFICATION			RELEASED	

<Requirement>

Appearance : No Damage

Contact Resistance :

Contact : Change from initial value: 30 m Ω maximum.

Shell : Change from initial value: 50 mΩ maximum.

Discontinuity : 1 μ sec maximum.

6.2 Humidity

<Test Condition A>

Mated connectors together and perform the test as follows.

Temperature : +25 to +85°C

Relative Humidity : 80 to 95%

Duration : 4 cycles (96 hours)

Upon completion of the test, specimens shall be conditioned at ambient room conditions for 24 hours, after which the specified measurements shall be performed.

(ANSI/EIA-364-31)

<Requirement>

Appearance : No Damage

Contact Resistance :

Contact :

Change from initial value: 30 mΩ maximum.

Shell :

Change from initial value: 50 mΩ maximum.

<Test Condition B>

Unmated each connectors and perform the test as follows.

Temperature : +25 to +85°C

Relative Humidity : 80 to 95%

Duration : 4 cycles (96 hours)

Upon completion of the test, specimens shall be conditioned at ambient room conditions for 24 hours, after which the specified measurements shall be performed.

(ANSI/EIA-364-31)

<Requirement>

Appearance : No damage

Dielectric Withstanding Voltage and Insulation Resistance :

Conform to item of dielectric withstanding voltage and insulation resistance

6.3 Thermal Aging

<Test Condition>

Mate connectors and expose to 105 ± 2°C for 250 hours. Upon completion of the exposure period, the test specimens shall be conditioned at ambient room conditions for 1 to 2 hours, after which

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

	TYPE PRODUCT SPECIFICATION	NUMBER GS-12-309	
TITLE HDMI CONNECTOR PLUG & RECEPTACLE		PAGE 7 of 10	REVISION B
		AUTHORIZED BY Leif Shen	DATE 28/10/04
		CLASSIFICATION RELEASED	

the specified measurements shall be performed.
(ANSI/EIA-364-17, Condition 4, Method A)

<Requirement>

Appearance : No Damage

Contact Resistance :

Contact :

Change from initial value: 30 m Ω maximum.

Shell :

Change from initial value: 50 m Ω maximum.

6.4 Industrial Mixed Flowing Gas (IMFG)

<Test Standard>: EIA 364-65, Class: III

<Duration>: 7 Days

<Condition>: Mated connectors


This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

Form E-3005
Rev A 02/12/01
V20603

GS-01-001

	TYPE PRODUCT SPECIFICATION	NUMBER GS-12-309	
	TITLE HDMI CONNECTOR PLUG & RECEPTACLE	PAGE 8 of 10	REVISION B
AUTHORIZED BY Leif Shen		DATE 28/10/04	
CLASSIFICATION RELEASED			

7.0 RECOMMENDED TEMPERATURE PROFILE



This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

	TYPE	PRODUCT SPECIFICATION		NUMBER	GS-12-309		
	TITLE			PAGE	9 of 10	REVISION	B
HDMI CONNECTOR PLUG & RECEPTACLE			AUTHORIZED BY		DATE		
			Leif Shen		28/10/'04		
			CLASSIFICATION				RELEASED

8.0 TEST SEQUENCE

	Test items	Test group									Test method
		1	2	3	4	5	6	7	8	9	
		Test sample q'ty									
		5	5	5	5	5	5	5	5	5	
Test sequence											
1	Contact resistance	1 3	1 3		1 3	1,3 5	2 4 7				4.1
2	Insulation resistance			1 4							4.3
3	Dielectric strength			2 5							4.2
4	Thermal shock	2									6.1
5	Humidity		2	3							6.2
6	Thermal aging				2						6.3
7	Vibration					2					5.1
8	Shock					4					5.2
9	Durability						3				5.3
10	Insertion/Withdrawal force						1 5				5.4
11	Current rating							1			4.4
12	Electrostatic discharge								1		4.6
13	Contact retention									1	
14	IMFG						6				

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

Form E-3005
Rev A 02/12/01
V20603

GS-01-001

	TYPE	PRODUCT SPECIFICATION		NUMBER	GS-12-309			
	TITLE			PAGE		10 of 10	REVISION	B
AUTHORIZED BY				DATE		28/10/04		
Leif Shen				28/10/04		CLASSIFICATION		RELEASED
HDMI CONNECTOR PLUG & RECEPTACLE								

REV.	PAGE	DESCRIPTION	EC#	DATE mm/dd/yyyy
A	All	New Release	T05-0041	04-28-2005
B	All	Add material spec. and SMT profile Add IMFG TEST ITEM	N06-0322	12-27-2006

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI Electronics. No part of the information shown on this document may be used in any way without the written consent of FCI Electronics.

Form E-3005
Rev A 02/12/01
V20603

GS-01-001