

# RJ45 1x4 Tab Down



## Specifications:

### Electrical

Contact Current Rating	: 1.5A Min.
Voltage Rating	: 150V AC (rms)
Withstanding Voltage	: 1,000V AC for 1 minute
Insulation Resistance	: 500MΩ Min.
Contact Resistance	: 50mΩ Max.

### Environmental


Operating Temperature	: -40°C to +85°C
Insertion & Extraction Force	: 18 Max.
Durability	: 750 Mating Cycled Min.

**RoHS  
Compliant**

## Material and Finish:

Housing	: Thermoplastic Plastic, Black, UL94 V-0
Insert	: Thermoplastic Plastic, Black, UL94 V-0
Terminal	: Phosphorous Bronze, T = 0.35mm 15μ" Plated in contact area Tin 80μ" Min. Plated in solder Tail
Shell	: Brass, T = 0.2mm Plated Ni 30μ" Min.

## Diagram




Dimensions : Millimetres



[www.element14.com](http://www.element14.com)  
[www.farnell.com](http://www.farnell.com)  
[www.newark.com](http://www.newark.com)



# RJ45 1×4 Tab Down



SUGGESTED PCB LAYOUT  
TOP VIEW  
DIMENSIONAL TOLERANCE: .XX±0.08



Dimensions : Millimetres

## Part Number Table

Description	Part Number
RJ45 Receptacle 8P8C 1×4 R/A DIP Type, Shielded with Led	MC001523

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.