



Main

| | |
|-----------------------------|----------------------------|
| Range | Spacial |
| Product name | Spacial S3DC |
| Device application | Multi-purpose |
| Product or component type | Compact enclosure |
| Enclosure nominal height | 400 mm |
| Enclosure nominal width | 300 mm |
| Enclosure nominal depth | 150 mm |
| Door type | Plain |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Without gland plate |
| Installation accessory type | Wall-mounting |
| Device composition | Lock 1 Door 1 Body 1 |



Complementary

| | |
|-----------------------------|---|
| Variant particularity | Single piece body Gutter-shaped front profile double sheet thickness |
| Number of doors | 1 front face |
| Door opening side | Reversible 120 ° |
| Lock type | Screw driver insert lock |
| Accessibility for operation | Front |
| Removable parts | Door by hinges |
| Material | Steel |
| Surface finish | Epoxy-polyester powder |
| Colour | Grey RAL 7035 |
| Standards | IEC 62208 |
| Product certifications | UL |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP66 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1040 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available  Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|