

# In-Line 6 Pin DIN Jack




RoHS  
Compliant



## Specifications

Rating	: 100V AC 1A Max.
Contact Resistance	: Pins-30mΩ Max.; Shell-50mΩ Max.
Insulation Resistance	: Min 100MΩ @500V DC
Voltage Withstand	: 250V AC R.M.S. For 1 Minute

## Diagram



No.	Part Name	Description	Qty.
1	Shell Cover	EVA+LLDPE	1
2	Shield Cover A	Steel, Nickel-Plated	
3	Shield Cover B	Steel, Nickel-Plated	
4	Housing	ABS	
5	Contact Terminals	Brass, Silver-Plated	6

Dimensions : Millimetres

## Part Number Table

Description	Part Number
In-Line 6 Pin DIN Jack	27-1680

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. MCM is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands  
Farnell.com/exclusive-brands  
Element14.com/exclusive-brands

