



Illuminated pushbutton actuator, RMQ-Titan, Extended, maintained, yellow, Blank, Bezel: titanium



Part no. M22-DRLH-Y  
216799  
EL Number 4355654  
(Norway)

General specifications		
Product name		Eaton Moeller® series M22 Illuminated pushbutton actuator
Part no.		M22-DRLH-Y
EAN		4015082167998
Product Length/Depth		30 millimetre
Product height		35 millimetre
Product width		30 millimetre
Product weight		0.013 kilogram
Compliances		CE Marked
Certifications		CSA Std. C22.2 No. 94-91 EN 60947-5 UL 508 CSA Std. C22.2 No. 14-05 IEC 60947-5 VDE CSA Class No.: 3211-03 UL File No.: E29184 CSA-C22.2 No. 14-05 CSA-C22.2 No. 94-91 CSA File No.: 012528 VDE 0660 IEC/EN 60947 UL UL Category Control No.: NKCR CE CSA IEC/EN 60947-5 LR DNV GL
Product Tradename		M22
Product Type		Illuminated pushbutton actuator
Product Sub Type		None
Features & Functions		
Bezel color		Titanium
Bezel material		Plastic
Design		Extended Classical
Fitted with:		Front ring
Functions		Stay-put/spring-return function can be changed on device
Inscription		Blank
Material		Titanium front ring
General information		
Degree of protection		NEMA 4X NEMA 3R IP66 NEMA 13 IP69K NEMA 12 IP67
Degree of protection (front side)		IP67/IP69K NEMA 4X
Lifespan, mechanical		1,000,000 Operations (AC operated)
Opening diameter		22.5 mm
Operating frequency		1800 Operations/h
Product category		RMQ-Titan
Size		Front diameter: 29.7 mm
Suitable for		Illumination

Type			Illuminated pushbutton actuator
<b>Ambient conditions, mechanical</b>			
Mounting position			As required
Shock resistance			30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
<b>Climatic environmental conditions</b>			
Ambient operating temperature - min			-25 °C
Ambient operating temperature - max			70 °C
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Communication</b>			
Connection to SmartWire-DT			Yes With SWD-RMQ connections
<b>Actuator</b>			
Actuating force			5 N
Actuator color			Yellow
Actuator function			Maintained Switching function latching
<b>Contacts</b>			
Force for positive opening - min			0 N
<b>Design verification</b>			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss13-27-37-12-10 [AKF028019])			
Colour button			Yellow
Number of command positions			1

Construction type lens		Round
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
Type of button		High
Suitable for illumination		Yes
With protective cover		No
Labelled		No
Switching function latching		Yes
Spring-return		No
With front ring		Yes
Material front ring		Plastic
Colour front ring		Titanium
Degree of protection (IP), front side		IP67/IP69K
Degree of protection (NEMA), front side		4X