

Straight 3.5mm Phone Jack


pro-SIGNAL



Specifications

Gender	: Jack
Contact Termination	: Solder Tag / Through Hole
Mounting Type	: Chassis
Pin Diameter	: 3.5mm
Connector Colour	: Black
Contact Resistance	: 30mΩ max
Insulation Resistance	: 100mΩ min at DC 500V
Dielectric Withstand Voltage	: AC 500V for one minute

Diagram



Dimensions : Millimetres

Material Specifications

No.	Parameter	Material	Plating
1	Earth Terminal	Phosphor Bronze (0.25T)	Silver
2	Ring Spring	Phosphor Bronze (0.25T)	Silver
3	Tip Spring	Phosphor Bronze (0.2T)	Silver
4	Housing	PBT	Black

Part Number Table

Description	Part Number
Straight 3.5mm Phone Jack, Solder Tag, Chassis, PBT, Black	PS000175

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. © Premier Farnell Limited 2016.