



SECTION Y-Y
ROTATED 90°

| | | | | | | | | | |
|--------------------------|-----------|-------|-------|-------|-------|-------|-------------------|----------------------------|-----------|
| 3 | 5-87483-4 | 1.675 | 1.775 | 3.700 | 1.500 | 1.600 | 64 | | 5-87483-3 |
| 3 | 5-87483-2 | 1.575 | 1.575 | 3.400 | 1.400 | 1.400 | 58 | 3 | 5-87483-1 |
| 3 | 5-87483-0 | 1.475 | 1.575 | 3.300 | 1.300 | 1.400 | 56 | 3 | 4-87483-9 |
| 3 | 4-87483-8 | 1.375 | 1.375 | 3.000 | 1.200 | 1.200 | 50 | 3 | 4-87483-7 |
| 3 | 4-87483-6 | 1.275 | 1.375 | 2.900 | 1.100 | 1.200 | 48 | 3 | 4-87483-5 |
| 3 | 4-87483-4 | 1.275 | 1.275 | 2.800 | 1.100 | 1.100 | 46 | 3 | 4-87483-3 |
| 3 | 4-87483-2 | 1.175 | 1.175 | 2.600 | 1.000 | 1.000 | 42 | 3 | 4-87483-1 |
| 3 | 4-87483-0 | 1.075 | 1.075 | 2.400 | .900 | .900 | 38 | 3 | 3-87483-9 |
| 3 | 3-87483-8 | .975 | 1.075 | 2.300 | .800 | .900 | 36 | 3 | 3-87483-7 |
| 3 | 3-87483-6 | .975 | .975 | 2.200 | .800 | .800 | 34 | 3 | 3-87483-5 |
| 3 | 3-87483-4 | .875 | .875 | 2.000 | .700 | .700 | 30 | 3 | 3-87483-3 |
| 3 | 3-87483-2 | .775 | .875 | 1.900 | .600 | .700 | 28 | 3 | 3-87483-1 |
| 3 | 3-87483-0 | .675 | .775 | 1.700 | .500 | .600 | 24 | 3 | 2-87483-9 |
| 3 | 2-87483-8 | .675 | .675 | 1.600 | .500 | .500 | 22 | 3 | 2-87483-7 |
| 3 | 2-87483-6 | .575 | .575 | 1.400 | .400 | .400 | 18 | 3 | 2-87483-5 |
| 3 | 2-87483-4 | .475 | .475 | 1.200 | .300 | .300 | 14 | 6 | 2-87483-3 |
| 3 | 2-87483-2 | .375 | .475 | 1.100 | .200 | .300 | 12 | 3 | 2-87483-1 |
| 3 | 2-87483-0 | .375 | .375 | 1.000 | .200 | .200 | 10 | 3 | 1-87483-9 |
| 3 | 1-87483-8 | .275 | .375 | .900 | .100 | .200 | 8 | 3 | 1-87483-7 |
| 5 | 1-87483-6 | .275 | .275 | .800 | .100 | .100 | 6 | | 1-87483-5 |
| 3 | 1-87483-4 | 1.375 | 1.475 | 3.100 | 1.200 | 1.300 | 52 | 3 | 1-87483-3 |
| 3 | 1-87483-2 | 1.175 | 1.275 | 2.700 | 1.000 | 1.100 | 44 | 3 | 1-87483-1 |
| 4 | 1-87483-0 | 1.075 | 1.175 | 2.500 | .900 | 1.000 | 40 | | 87483-9 |
| 3 | 87483-8 | .875 | .975 | 2.100 | .700 | .800 | 32 | 3 | 87483-7 |
| 3 | 87483-6 | .775 | .775 | 1.800 | .600 | .600 | 26 | 3 | 87483-5 |
| 3 | 87483-4 | .575 | .675 | 1.500 | .400 | .500 | 20 | | 87483-3 |
| 3 | 87483-2 | .475 | .575 | 1.300 | .300 | .400 | 16 | 3 | 87483-1 |
| MARKED PART NUMBER | | E | D | C | B | A | NO. OF POSN | UMMARKED PART NUMBER | |

| | | | | | | | |
|---|--|--|--|---|-----------|------------|---------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN 12-27-89 R. SCHLAG BG CHK P.SREMCICH 10-5-93 APVD P.SREMCICH 10-5-93 | |  TE Connectivity | | | |
| DIMENSIONS: INCHES | | TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ANGLES ± - | | NAME CONNECTOR, CRIMP SNAP-IN, MOD IV, DOUBLE ROW, .100 C/L, SHORT ENTRY | | | |
|  | | PRODUCT SPEC - APPLICATION SPEC - | | | | | |
| MATERIAL GLASS FILLED NYLON COLOR-BLACK PER ASTM D4066 | | FINISH - | | SIZE | CAGE CODE | DRAWING NO | RESTRICTED TO |
| | | WEIGHT - | | A2 | 00779 | C-87483 | - |
| CUSTOMER DRAWING | | | | SCALE | 4:1 | SHEET | 1 of 1 |
| | | | | | | REV | V2 |