




3 In case that the application demands a high level of reliability, such as automotive, please contact a company representative for further information.

TO



HRS NO	PART NO	A	B
CL541-0200-6	DF1B-2S-2.5R	5.0	2.5
CL541-0201-9	DF1B-3S-2.5R	7.5	5.0
CL541-0202-1	DF1B-4S-2.5R	10.0	7.5
CL541-0203-4	DF1B-5S-2.5R	12.5	10.0
CL541-0204-7	DF1B-6S-2.5R	15.0	12.5
CL541-0205-0	DF1B-7S-2.5R	17.5	15.0
CL541-0206-2	DF1B-8S-2.5R	20.0	17.5
CL541-0207-5	DF1B-9S-2.5R	22.5	20.0
CL541-0208-8	DF1B-10S-2.5R	25.0	22.5
CL541-0209-0	DF1B-11S-2.5R	27.5	25.0
CL541-0210-0	DF1B-12S-2.5R	30.0	27.5
CL541-0211-2	DF1B-13S-2.5R	32.5	30.0
CL541-0212-5	DF1B-14S-2.5R	35.0	32.5
CL541-0213-8	DF1B-15S-2.5R	37.5	35.0
CL541-0214-0	DF1B-16S-2.5R	40.0	37.5
CL541-0215-3	DF1B-18S-2.5R	45.0	42.5
CL541-0216-6	DF1B-20S-2.5R	50.0	47.5

NOTE 1 2 positions socket have one polarizing slot at senter.  
3 TO 6 positions have 2 polarizing slots at both ends.  
Other positions have 3 polarizing slots as per drawing.

CODE NO. (OLD) CL		DRAWN Y. Inoue		DESIGNED Y. Inoue		CHECKED T. Miyagaki		APPROVED K. Katayama		RELEASED	
SCALE 2 : 1		DRAWING NO. EDC3-160017		PART NO. DF1B-*S-2.5R		POLYAMIDE		NATURAL (WHITE), UL94V-0		FINISH, REMARKS	
UNITS mm		HIROSE ELECTRIC CO., LTD		CODE NO. CL541		1		7		8	