



Main

| | |
|---------------------------|---|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch head |
| Device short name | ZCE |
| Head type | Plunger head |
| Product compatibility | XCKD XCKP XCKT XCMD |
| Associated body | ZCD21 ZCD21M12 ZCD25 ZCD26 ZCD27 ZCD28 ZCD29 ZCD29M12 ZCD31 ZCD35 ZCD37 ZCD39 ZCMD21C12 ZCMD21L08R12 ZCMD21L08U78 ZCMD21L1 ZCMD21L2 ZCMD21L5 ZCMD21M12 ZCMD25L1 ZCMD25L2 ZCMD25L5 ZCMD29C12 ZCMD29L1 ZCMD29L2 ZCMD29L5 ZCMD37L1 ZCMD37L2 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCMD37L5
 ZCMD39L1
 ZCMD39L2
 ZCMD39L5
 ZCMD41L1
 ZCMD41L2
 ZCMD41L5
 ZCMD61C12
 ZCMD61M12
 ZCMD69C12
 ZCMD81L1
 ZCMD81L2
 ZCMD81L5
 ZCP21
 ZCP21M12
 ZCP25
 ZCP26
 ZCP27
 ZCP28
 ZCP29
 ZCP29M12
 ZCP31
 ZCP35
 ZCP37
 ZCP39
 ZCT21G11
 ZCT21N12
 ZCT21P16
 ZCT25G11
 ZCT25N12
 ZCT25P16
 ZCT26G11
 ZCT26N12
 ZCT26P16
 ZCT27G11
 ZCT27N12
 ZCT27P16
 ZCT28G11
 ZCT28N12
 ZCT28P16

| | |
|----------------------------|--|
| Movement of operating head | Linear |
| Type of operator | Roller lever plunger spring return thermoplastic |
| Type of approach | Lateral or vertical approach 1 direction |

Complementary

| | |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0953 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|