



### Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XSE
Sensor design	Form 26 x 26 x 45
Size	64 mm
Body type	Fixed
Enclosure material	Nickel plated brass
Type of output signal	Discrete
Wiring technique	2-wire
[Sn] nominal sensing distance	10 mm
Discrete output function	1 NO
Electrical connection	4 pins M12 male connector
[Us] rated supply voltage	12...48 V DC
Switching capacity in mA	3...100 mA
IP degree of protection	IP67

### Complementary

Detector flush mounting acceptance	Flush mountable
Material	Metal
Front material	Plastic
Output circuit type	DC
Supply voltage limits	10...58 V DC
Switching frequency	<= 40 Hz
Marking	CE
Depth	26 mm
Height	45 mm
Width	26 mm
Product weight	0.08 kg

## Environment

Product certifications	CCC
Ambient air temperature for operation	-25...70 °C

## Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2013 Will be compliant on 3Q2013
------------------------	--

## Contractual warranty

Warranty period	18 months
-----------------	-----------

XSEC107130D4 is replaced by the following group of products:



### Inductive sensors XS XS7E1A1CAL01M12

inductive sensor XS7 26x26x13 - PBT - Sn10mm - 12..24VDC - M12 0.15m

Qty 1



### Accessories XSZBE10

accessory for sensor - replacement bracket

Qty 1

Reason for Substitution: End of life | Substitution date: 30 December 2006