

ZCKJD39

limit switch body ZCKJ - fixed - w/o display - 2NC
+1NO - snap action - Pg13



Main

| | |
|-------------------------------|--|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch body |
| Device short name | ZCKJ |
| Body type | Fixed |
| Product compatibility | XCKJ |
| Associated head | ZCKE62 ZCKE629 ZCKE05 ZCKE23 ZCKE63 ZCKE21 ZCKE64 ZCKE66 ZCKE65 ZCKE06 ZCKE08 ZCKE619 ZCKE67 ZCKE61 |
| Body material | Metal |
| Cable entry | 1 entry tapped for Pg 13.5 cable gland |
| Number of poles | 3 |
| Contacts type and composition | 2 NC + 1 NO |
| Contact operation | Snap action |
| Number of steps | 1 1 position |
| Contacts material | Silver plated contacts |

Complementary




| | |
|-----------------------|---|
| Local display | Without |
| Electrical connection | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 0.75 mm² |

| | |
|--|---|
| Positive opening | With |
| Minimum actuation speed | 0.01 m/min |
| [Ie] rated operational current | 1.5 A at 240 V, AC-15, B300 conforming to EN/IEC 60947-5-1 appendix A 0.1 A at 250 V, DC-13, R300 conforming to EN/IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 6 A |
| [Ui] rated insulation voltage | 400 V (pollution degree 3) conforming to IEC 60947-1for contact block 300 V conforming to CSA C22.2 No 14for contact block 300 V conforming to UL 508for contact block |
| Maximum resistance across terminals | 0.25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60664 6 kV conforming to IEC 60947-1 |
| Short-circuit protection | 10 A cartridge fuse, type gG |
| Electrical durability | 5000000 cycles, DC-13 120 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 13 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 9 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width | 52 mm |
| Height | 72 mm |
| Depth | 30 mm |
| Net weight | 0.21 kg |
| Terminals description ISO n°1 | (13-14)NO (21-22)NC |

Environment

| | |
|---------------------------------------|-------------------------------------|
| IP degree of protection | IP66 |
| IK degree of protection | IK05 |
| Ambient air temperature for operation | -25...70 °Cfor standard environment |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|