



## Main

|                               |                       |
|-------------------------------|-----------------------|
| Range of product              | OsiSense XC           |
| Product or component type     | Pre-cabled connection |
| Component name                | ZCMC                  |
| Associated body               | ZCMD29                |
| Number of poles               | 2                     |
| Contacts type and composition | 2 NC                  |
| Contact operation             | Snap action           |

## Complementary

|                          |        |
|--------------------------|--------|
| Product compatibility    | XCMD29 |
| Electrical connection    | Cable  |
| Cable length             | 2 m    |
| Wire insulation material | PvR    |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0937 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available<br><a href="#">Product Environmental Profile</a>  |
| Product end of life instructions | Need no specific recycling operations<br><a href="#">End of Life Information</a>  |

Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|