

Dec.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1						2						3						4					
		△數	訂正事項				擔當	檢圖	年月日				△數	訂正事項				擔當	檢圖	年月日			
		COUNT	DESCRIPTION OF REVISIONS				B	Y	DATE				COUNT	DESCRIPTION OF REVISIONS				B	Y	DATE			
△									. .		△								. .				
△									. .		△								. .				
△									. .		△								. .				

A

B

C

D

E

F

Top View Dimensions:  
Overall width: 9.9 ±0.3  
Pin diameter: 1.35 ±0.2  
Pin height: 6.2 ±0.3  
Base diameter: 3 ±0.3  
Pin to base distance: 0.7 ±0.2

Side View Dimensions:  
Overall height: 3.1 ±0.2  
Pin height: 0.9 ±0.2  
Base height: 1.2 ±0.2  
Pin to base distance: 0.8 ±0.2  
Pin to base distance: 0.7 ±0.2  
Pin to base distance: 2.05 ±0.2

Callout 1: Points to the top of the pin.

NOTE1. ONE REEL HAS 10,000 PIECES OF CONTACTS.

			1	PHOSPHOR BRONZE	TIN PLATED 1μm MIN.				
NO.	MATERIAL	FINISH.	REMARKS	NO.	MATERIAL	FINISH.			
CODE NO. (OLD)				DRAWN		DESIGNED	CHECKED	APPROVED	RELEASED
				CHOI 17.12.22 J.S		CHOI 17.12.22 J.S	LIM 17.12.22 S.M	KANG 17.12.22 T.S	
		DRAWING NO. EDC4-611492		PART NO. DF51K-2428SCF (800)					
SCALE 10:1		HRS HIROSE KOREA CO.,LTD.		CODE NO 6652-0040-3-800					1/1
UNITS mm									

1

2

3

4