



### Main

Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKT XCMD XCKP XCKD
Associated body	ZCP26 ZCT21N12 ZCMD37L1 ZCD37 ZCMD21L1 ZCT27G11 ZCP21 ZCT21P16 ZCMD21M12 ZCP27 ZCP37 ZCMD29C12 ZCT26P16 ZCT28P16 ZCMD69C12 ZCP31 ZCP35 ZCMD29L2 ZCD39 ZCP21M12 ZCMD21L2 ZCMD81L1 ZCMD37L5 ZCMD29L1 ZCMD39L2 ZCD28 ZCT28N12 ZCT26G11 ZCMD39L1 ZCMD61M12 ZCMD21L08U78 ZCD25 ZCT27P16 ZCD35

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

ZCMD41L5  
 ZCMD25L2  
 ZCMD81L2  
 ZCMD29L5  
 ZCT25P16  
 ZCD27  
 ZCD29  
 ZCT25N12  
 ZCMD21L08R12  
 ZCMD39L5  
 ZCP28  
 ZCT21G11  
 ZCD26  
 ZCP25  
 ZCT27N12  
 ZCMD41L2  
 ZCP39  
 ZCMD61C12  
 ZCMD21L5  
 ZCT25G11  
 ZCMD25L1  
 ZCD21M12  
 ZCD21  
 ZCP29M12  
 ZCT26N12  
 ZCD29M12  
 ZCT28G11  
 ZCD31  
 ZCMD37L2  
 ZCMD41L1  
 ZCP29  
 ZCMD81L5  
 ZCMD21C12  
 ZCMD25L5

Movement of operating head	Linear
Type of operator	End plunger spring return metal
Type of approach	Vertical approach 1 direction

### Complementary

Positive opening	With
------------------	------

### Environment

Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

### Contractual warranty

Warranty period	18 months
-----------------	-----------