

Product Information

Order Code / Sku	4434468
Product Details	SWITCH, ANTI-VANDAL RED; Approval Bodies: IP67; Diameter, panel cut-out: 19.25mm; Length / Height, external: 33.5mm; Switch function type: SPNO+SPNC; Temperature, operating (a) max: 105°C; Temperature, operating (a) min:
Description	SWITCH, ANTI-VANDAL RED; Approval Bodies: IP67; Diameter, panel cut-out: 19.25mm; Length / Height, external: 33.5mm; Switch function type: SPNO+SPNC; Temperature, operating (a) max: 105°C; Temperature, operating (a) min: -30°C; Voltage, contact AC max: 250V; Voltage, contact DC max: 5V; Colour: Red; Current, contact @ contact voltage AC max: 10A; Current, contact @ contact voltage DC max: 10mA; Depth, behind panel: 31mm; Diameter, bezel: 21.5mm; Dielectric strength, VDC: 1kV ac 1 minute; Force, operating: 2.6N; Material, contact: Silver; Operations, electrical number of: 500000; Resistance, contact: 25mR; Resistance, insulation: 1000MR @500V dc; Thickness, panel max: 8mm; Thickness, panel min: 1.5mm
Pack Details	1
Catalogue Page Number	/
Manufacturer	ITW SWITCHES
Manufacturer Part Number	76-959033
Family Pricing Code	0
Stock Availability	In Stock

**SPNO and SPNC Momentary**

10mA @5V dc, 10A @ 250V acIP67 Sealed
 Bezel dia=21.5, D(behind panel)=31, Panel cut-out dia = 19.25

- Vandal resistant
- Attractively machined in stainless steel, available in six colours
- Low profile bezel protrudes only 2.5mm
- Solder terminals
- Panel sealed to IP67

Contacts	Silver	Insulation resistance	1000 MR
----------	--------	-----------------------	---------

Other Product Images

Contact resistance	25 mR	Electrical life	500000 ops
Dielectric strength	1 kV ac	Operating temperature	-30 °C to + 105 °C

		Price Each
Colour	Order Code	
Red	443-4468	
Green	443-4470	
Black	443-4481	
Gold	443-4493	
Blue	443-4500	
Purple	443-4511	