Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case that the application demands a high level of reliability, such as automotive,
please contact a company representative for further information.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
				. .
				. .
				. .

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
				. .
				. .
				. .







RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE) (2:1)



A－A



NOTE 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
2. FOR MODIFICATION,ETC.,PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH, REMARKS
1	PPS	LIGHT BROWN (UL94V-0)
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min. LEAD AREA:TIN-PLATING 1μm min. UNDER PLATING:NICKEL 1μm min.

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	K.NAKAMURA 05.12.16	K.NAKAMURA 05.12.16	H.Ozawa '05.12.16	H.Okawa 05.12.16	

SCALE	DRAWING NO.	PART NO.
5 : 1	EDC3-150833-25	FX8C-100P-SV1(71)
UNITS mm	HRS HIROSE ELECTRIC CO.,LTD.	CODE NO. CL578-0525-7-71 1/1

TO
PCK

HRS DRAWING FOR REFERENCE