

## UL PICCOLO UL PC C 85 T



Sample photo

**Order symbol:** UL PC C 85 T  
**Product nbr:** 8714006  
**Description:** UL Enclosure, PC  
**Remarks:** Transparent cover

**EAN:** 6418074038869  
**El. number:**  
**Finland:**  
**Electric No.** 8212031089  
**Denmark:**  
**Electric No. Italy:** 7202025U

Including: Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

Dimensions:				Rating:
Length	Width	Height		
mm:	140	80	85	Ingress Protection (EN 60529): IP66/IP67
inch:	5.5	3.1	3.3	Impact Resistance (EN 62262): IK08
				Electrical insulation: Totally insulated
				Halogen free (DIN/VDE 0472, Part 815): 1
				UV resistance: UL 508
				Flammability Rating: UL 746C 5"
				UL Type:
				Glow Wire Test (IEC 695-2-1) °C: 960
Materials:				Certificates:
Material:	Polycarbonate			Germanischer Lloyd (GL)
Base colour:	RAL 7035 -light grey			Underwriters Laboratories
Cover screws material:	Polyamide			SGS Fimko
Cover colour:	Clear transparent			UL Canada
Cover screws colour:	Grey			Gost R
Gasket material:	Polyurethane			
Temperatures:				
Temperature °C (short term):	-40 ... 120 °C			
Temperature °C (continuous):	-40 ... 80 °C			
Temperature °F (short term):	-40 ... 250 °F			
Temperature °F (continuous):	-40 ... 175 °F			

PICCOLO 140x80x65-85

