



**Order symbol:** ARK864CHFSSL  
**Product nbr:** 8561408  
**Description:** PC Enclosure  
**Remarks:** Hinged opaque flat cover w/S.S. Lockable latch. Base includes 1/2 and 3/4 inch knock-outs

**EAN:** 6418074095848  
**EI. number:**  
**Finland:**

Including: Hinged cover. Base with 10-32 brass inserts, latched flat cover with formed in place PUR gasket, stainless hinge pin. Base with 1/2 and 3/4 inch knock-outs. Quick release latches. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Sample photo

Dimensions:	Length	Width	Height	Accessories:	
mm:	203	152	101	ALBP86	Aluminum Back Panel
inch:	8.0	6.0	4.0	ADFP86	Dead Front Panel w/ screws
				ASP86	Aluminum Swing Panel
				ASPK86	Swing Panel Kit incl. Panel
				ASPHK8	Swing Panel Kit w/o Panel
				AMFL6	6" Mounting Flange Set
Materials:				Rating:	
<b>Material:</b>	Polycarbonate			Ingress Protection (EN 60529):	IP66/IP67
<b>Base colour:</b>	RAL 7035 -light grey			Impact Resistance (EN 62262):	IK09
<b>Cover screws material:</b>	Stainless steel			Electrical insulation:	Totally insulated
<b>Cover colour:</b>	RAL 7035 -light grey			Halogen free (DIN/VDE 0472, Part 815):	1
<b>Gasket material:</b>	Polyurethane			UV resistance:	UL 508
				Flammability Rating:	UL 508
				Glow Wire Test (IEC 695-2-1) °C:	960
				NEMA Class:	NEMA 4, 4X, 6, 6P, 12, 13
Temperatures:				Certificates:	
<b>Temperature °C (short term):</b>	-40 ... 140 °C			Gost R	
<b>Temperature °C (continuous):</b>	-40 ... 80 °C				
<b>Temperature °F (short term):</b>	-40 ... 284 °F				
<b>Temperature °F (continuous):</b>	-40 ... 175 °F				
Accessories:					
ABP86	Painted Steel Back Panel				

