

Guided actuator DFM-20-100-P-A-KF

Part number: 170921

FESTO



Data sheet

Feature	Value
Distance of centre of gravity of payload to yoke plate xs	50 mm
Max. static moment Mx	29.58 Nm
Max. static moment My	18.87 Nm
Max. permissible torque load Mx as a function of the stroke	2.95 Nm
Max. force Fz static	1020 N
Max. force Fy static	1020 N
Center of gravity of the moving mass as a function of the stroke	59.4 mm
Max. static moment Mz	18.87 Nm
Max. force Fy	817 N
Max. force Fz	817 N
Max. torque My	15.11 Nm
Max. torque Mz	15.11 Nm
Stroke	100 mm
Piston diameter	20 mm
Type code	DFM
Drive unit operating mode	Yoke
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Guide	Recirculating ball bearing guide
Design	Guide
Position sensing	For proximity sensor
Symbol	00991737
Operating pressure	2 bar ... 10 bar
Max. speed	0.8 m/s
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	0 - No corrosion stress
Ambient temperature	-5 °C ... 60 °C
Impact energy in the end positions	0.2 J
Max. torque Mx	23.69 Nm
Max. payload as a function of the stroke at defined distance xs	78 N
Theoretical force at 6 bar, retracting	141 N
Theoretical force at 6 bar, advancing	188 N
Moving mass	632 g
Product weight	1468 g

Feature	Value
Alternative connections	See product drawing
Pneumatic connection	M5
Note on materials	Free of copper and PTFE RoHS-compliant
Cover material	Wrought aluminum alloy
Seals material	NBR
Housing material	Wrought aluminum alloy
Piston rod material	High-alloy stainless steel