


Pneumatic valve VL/O-3-1/2

Part number: 9983

FESTO



Data sheet

Feature	Value
Valve function	3/2, open/closed, monostable
Lap	Underlap
Actuation type	Pneumatic
Width	52 mm
Standard nominal flow rate	3700 l/min
Pneumatic working port	G1/2
Operating pressure	-0.95 bar ... 10 bar
Design	Plate seat
Reset method	Mechanical spring
Nominal width	14 mm
Width dimension	69 mm
Type code	VL/O
Exhaust air function	With flow control option
Sealing principle	Soft
Mounting position	Any
Manual override	None
Type of control	Direct
Pilot air supply port	External
Flow direction	Reversible
Symbol	00991030
Pilot pressure	1 bar ... 10 bar
b-value	0.3
Switching time off	30 ms
On switching time	17 ms
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
Storage temperature	-20 °C ... 60 °C
Temperature of medium	-10 °C ... 60 °C
Pilot medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Ambient temperature	-10 °C ... 60 °C
Product weight	860 g
Type of mounting	On terminal strip With through-hole Optionally:
Pilot air port 110	G1/4

Feature	Value
Pilot air port 12	G1/4
Pneumatic connection 1	G1/2
Pneumatic connection 11	G1/2
Pneumatic connection 2	G1/2
Pneumatic connection 3	G1/2
Pneumatic connection 33	G1/2
Note on materials	RoHS-compliant
Seals material	NBR
Housing material	Die-cast aluminum