






RECOMMENDED METAL MASK THICKNESS : 120 $\mu$ m  
RECOMMENDED METAL MASK OPENING RATIO : 80% FOR LEAD PAD

- NOTES
1. ALL LEADS AND REINFORCED METAL FITTINGS CO-PLANARITY SHALL BE 0.1mm MAX.
  2.  IS NO PATTERN AREA OTHER THAN THE SAME CIRCUIT.
  3. HRS MARK AND CAV NO. IS INDICATED IN APPROXIMAL POSITION SHOWN.
  4.  GATE POSITION IS POSITIONED IN APPROXIMAL AREA SHOWN.  
A PART OF THE WALL COULD BE NOTCHED FOR SETTING GATE.

UNITS mm		SCALE 10: 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.	APPROVED	・MO. ISHIDA		15. 07. 15	DRAWING NO.	EDC-315044-58-01		
	CHECKED	・TS. MIYAZAKI		15. 07. 15	PART NO.	DF40C(2. 0)-40DS-0. 4V(58		
	DESIGNED	・SH. HOSODA		15. 07. 15	CODE NO.	CL684-4042-5-58		
	DRAWN	・KR. AJITO		15. 07. 15		 		

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

