



1. THIS PLUG WILL MATE WITH ANY RECEPTACLE CONNECTOR WITH THE SAME INSERT ARRANGEMENT AS DEFINED BY MS18277-1.
2. MAXIMUM WIRE INSULATION USED WITH THIS PLUG IS .072 [1.83] DIA.
3. Be-Cu RETENTION CLIPS ARE INCLUDED IN INSERTS.
4. UL/CSA DESIGNATION STAMPED IN THIS AREA, OPTIONAL.
5. RESTRICTED TO CAE ELECTRONIC ONLY.
6. THESE CONNECTORS ARE QUALIFIED TO GODDARD SPACE FLIGHT CENTER SPECIFICATION S-311-P-4.
7. CONTACT NOT INCLUDED - SHOWN FOR DIMENSIONAL REFERENCE ONLY.
8. FAR SIDE REFERS TO WIDE SIDE OF KEYSTONE.

	.120 [3.05]	1A01-031PHA	206804-5	206804-5
	.120 [3.05]	311P409-5P-B-12	206804-2	206804-4
	.154 [3.91]	N/A	206804-3	206804-3
	.120 [3.05]	311P409-5P-B-12	206804-2	206804-2
	.154 [3.91]	311P409-5P-B-15	206804-1	206804-1
REMARKS	DIA A	CUSTOMER P/N ON CONNECTOR	MFG P/N ON CONNECTOR	MFG P/N

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A.J. GRAFF 12-23-92	TE Connectivity	
DIMENSIONS: INCHES		CHK B.GILLMAN 12-24-92		
	TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
	0 PLC ± .005		PRODUCT SPEC	
	1 PLC ± .005		MIL-C-24308	
	2 PLC ± .005		APPLICATION SPEC	
MATERIAL SEE CALLOUTS		WEIGHT —	SIZE A1	RESTRICTED TO
SEE CALLOUTS		CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1