



**1-CONDUCTOR PCB TERMINAL  
STRIP 2 SOLDER PINS / POLE PIN  
SPACING 5/5.08 MM / 0.2 IN WITH  
PUSH BUTTONS**  
235-402/331-000 TO 235-448/331-000

|  |   |
|--|---|
| ITEM-NO. (ITEM-NO.)                                  | 235-408/331-000                           |
| Cross section1 (Cross section / mm <sup>2</sup> )    | 0.5 - 1.5                                 |
| Cross section2 (Cross section / AWG)                 | 20 - 16                                   |
| Strip length (Strip length / mm)                     | 9 - 10                                    |
| Measured voltage (Measured voltage / V)              | 320                                       |
| Measured shock voltage (Measured shock voltage / kV) | 4   |
| Pollution degree (Pollution degree)                  | 2   |
| Current intensity (Current intensity / A)            | 17.5                                      |
| RM (PIN SPACING / mm)                                | 5   |
| P (NO. OF POLES)                                     | 8   |
| Height (Height / mm)                                 | 15.5                                      |
| Width (Width / mm)                                   | 41.5                                      |
| Depth (Depth / mm)                                   | 12.5                                      |
| No. of connection Points (No. of connection Points)  | 8   |
| No. of potentials (No. of potentials)                | 8   |
| COLOR (COLOR)  | grau                                      |
| WEIGHT (WEIGHT / g)                                  | 6.118                                     |
| Comment (Comment)                                    | L = (No. of poles x Pin Spacing) + 1,5 mm |
| Dimensions (Dimensions)                              | 1 +0,1 mm                                 |