



RoHS compliant

3	10	Signal contact	S0 / Brass	AuroPur / AWG20
2	1	Shell	Steel	tin plated
1	1	Insulator	PBT (-55°C - +130°C)	green
<i>No.</i>	<i>St.</i>	<i>Part</i>	<i>Type Description/Material</i>	<i>Surface plating/Colour/Class</i>

			 <p>Measurement without tolerance acc. to ISO 2768-m</p>	<p>SCALE 2:1</p>	<p>TITLE</p> <p>D-Sub Mixed-Layout Connector</p>	<p>REV.</p> <p>1</p>	
							<p>NAME / DATE</p>
		<p>DRAWN</p>					<p>sschref 09-04-2014</p>
		<p>CHECKED</p>					<p>sschref 09-04-2014</p>
							 <p>a molex company</p>
1							
REV.	DATE	CH.-NO.	ORIGINAL: DIN A3-DRAWING AS A FILE	REPLACEMENT FOR:		PAGES	

COMMENT:
ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING, WITHOUT OUR PRIOR CONSENT,
IT MAY NEITHER BE DUBLICATED NOR MADE AVAILABLE TO A THIRD PARTY,
AND IT ALSO MAY NOT BE IMPROPERLY USED BY TE RECEIVER, OR A THIRD PARTY.