


## Zack marker strip - ZB10,LGS:FORTL.ZAHLEN - 1053014

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed horizontally: Consecutive numbers 1 - 10, 11 - 20, etc. up to 991 - 1000, Mounting type: Snap into tall marker groove, for terminal block width: 10.2 mm, Lettering field: 10.15 x 10.5 mm

The illustration shows versions  
ZB 10 - UNPRINTED, -  
LGS:CONSEC.NOS, -  
QR:CONSEC.NOS and -SO/CMS

### Why buy this product

- Labeling service: Phoenix Contact can custom-label all zack marker strip markers according to your requirements
- The ZB zack marker strip system is a marking solution for modular terminal blocks and electronics modules with tall marker grooves



### Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
Weight per Piece (excluding packing)	2.310 g
Custom tariff number	49119900
Country of origin	Germany

### Technical data

#### Dimensions

Width (a)	10 mm
-----------	-------

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
---------------------------------	-------------------

#### General

Note	10 identically marked strips make up one packing unit (PU).
Color	white
Components	free from silicone and halogen
Flammability rating according to UL 94	V2
Material	PA
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)

## Zack marker strip - ZB10,LGS:FORTL.ZAHLEN - 1053014

### Technical data

#### General

	VDE 0411-1
Printing direction	Printed horizontally
Printing	Consecutive numbers 1 - 10, 11 - 20, etc. up to 991 - 1000
Number of individual labels	10
Number of individual labels per row	10
Number of marker strips	10
Marking mounting type	Snap into tall marker groove

#### Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
	VDE 0411-1
Flammability rating according to UL 94	V2