



## NOTE:

## MATERIAL

HOUSING

FLANGE

CONTACT

SHELL

O-RING

SEALING COMPOUND

HARDWARE

PBT UL94V-0, BLACK

PBT UL94V-0, BLACK

BRASS, PLATING P/N KEY BELOW

STEEL, NICKEL

SILICONE

EPOXY

BRASS; NICKEL PLATED

## ELECTRICAL

SIGNAL CONTACT RATED CURRENT

5A

POWER CONTACT RATED CURRENT

P/N KEY BELOW

VOLTAGE

1000 VAC 1 MIN

INSULATOR RESISTANCE

5 GOhms MIN.

SIGNAL CONTACT RESISTANCE

10 mOhms MAX.

POWER CONTACT RESISTANCE

1.0 mOhms MAX.

WATER PROOF

IP67

## ENVIRONMENT

OPERATION TEMPERATURE

-25°C TO +85°C

SERIES

CDF = COMBO DSUB FLANGE

CONTACT TYPE

S = SOLDER CUP

POSITION

13W3

GENDER

2 = FEMALE

POWER CONTACT AMPERAGE

2 = 20 AMPS

4 = 40 AMPS

HARDWARE OPTIONS

1 = 4-40 THREADED INSERTS/4-40 JACKSCREWS

CONTACT PLATING OPTIONS

1 = GOLD FLASH

2 = 30u" GOLD PLATING

CDFS13W3203LYYY

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

J. KADEL

DATE:

04/27/2020

## TOLERANCES

X.  $\pm$ 0.40.X  $\pm$ 0.30.XX  $\pm$ 0.20.XXX  $\pm$ 0.10

UNITS = mm

DO NOT SCALE FROM DRAWING

NorComp

SCALE:

NTS

SHEET

1

OF

1

REV

0

DWG NO.

CDFS13W3203LYYY