

NSYEBCD12611

Enclosed power distribution block - CU lug, line 1, load 1, 600V 200A CU

Product availability : Stock - Normally stocked in distribution facility



Main

Range of product	NSYEB
Product or component type	Power Distribution Block

Complementary

System Voltage	600 V AC/DC
[In] rated current	200 A copper
Mounting support	35 mm DIN rail
Electrical connection	Tin plated copper lugs
Number of terminals	1 line 1 load
Number of cables	Line 1, AWG 14...AWG 3/0, copper Load 1, AWG 14...AWG 3/0, copper
Short-circuit current	100 kA
Material	Thermoplastic : block
Colour of enclosure	Grey
Wire stripping length	0.88 in Line 0.88 in Load
Connections - terminals	Lug 180 lbf.in AWG 8...AWG 3/0 copper line Lug 50 lbf.in AWG 14...AWG 10 copper line Lug 180 lbf.in AWG 8...AWG 3/0 copper load Lug 50 lbf.in AWG 14...AWG 10 copper load
Height	3.61 in
Width	1.21 in
Tightening torque	Line : 180 lb.in, AWG 8...AWG 3/0, copper Line : 50 lb.in, AWG 14...AWG 10, copper Load : 180 lb.in, AWG 8...AWG 3/0, copper Load : 50 lb.in, AWG 14...AWG 10, copper
Depth	2.71 in

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product certifications	CE UL listed file E323110 CCN QPQS CSA file 70361 class 6228 01
Dielectric strength	1000 V, maximum wire size: 70 mm ² conforming to IEC 60947-7-1
Ambient air temperature for operation	-40...257 °F

Ordering and shipping details

Category	21713 - IEC ENCLOSED POWER DISTR BLOCKS
Discount Schedule	CP1
GTIN	00785901463771
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5500000000000004
Returnability	Y
Country of origin	US