

Product availability : Stock - Normally stocked in distribution facility



Main

Range of product	NSYEB
Product or component type	Power Distribution Block

Complementary

System Voltage	600 V AC/DC
[In] rated current	510 A copper
Mounting support	Panel
Fixing mode	By screws M6 By screws 1/4 inch
Electrical connection	Tin plated copper lugs
Number of terminals	2 line 2 load
Number of cables	Line 2, AWG 6...250 kcmil, copper Load 2, AWG 6...250 kcmil, copper
Short-circuit current	100 kA
Material	Thermoplastic : block
Colour of enclosure	Grey
Wire stripping length	1.38 in Line 1.38 in Load
Connections - terminals	Lug 275 lbf.in AWG 1...250 kcmil copper line Lug 120 lbf.in AWG 6...AWG 2 copper line Lug 275 lbf.in AWG 1...250 kcmil copper load Lug 120 lbf.in AWG 6...AWG 2 copper load
Height	4.39 in
Width	2.26 in
Tightening torque	Line : 275 lb.in, AWG 1...250 kcmil, copper Line : 120 lb.in, AWG 6...AWG 2, copper Load : 275 lb.in, AWG 1...250 kcmil, copper Load : 120 lb.in, AWG 6...AWG 2, copper

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	3.14 in
Product compatibility	NSYEBP250 (250 kcmil)

Environment

Product certifications	CE CSA file 70361 class 6228 01 UL recognized E60616 CCN XCFR2
Dielectric strength	1000 V, maximum wire size: 120 mm ² conforming to IEC 60947-7-1
Ambient air temperature for operation	-40...257 °F

Ordering and shipping details

Category	21713 - IEC ENCLOSED POWER DISTR BLOCKS
Discount Schedule	CP1
GTIN	00785901619178
Nbr. of units in pkg.	1
Package weight(Lbs)	1.95
Returnability	Y
Country of origin	US