

MICRO SWITCH

A DIVISION OF HONEYWELL-ROTHWELL TOOLING COMPANY
FREDERICK, MARYLAND

FED. MFR. CODE 91929

SWITCH-BASIC

CATALOG LISTING

BZ-2RW896-A2

BZ-2RW896-A2

PAGE 1 OF 1

M

DRAWING
NUMBER

ISSUE
6

REPLACES

RELEASE NO. SR 4821

CNT 3 NOV. 55

CHECK

RWL 4 NOV. 55

CHECK

DLT 14 SEP 98

CHECK

GEN 2 NOV. 55

CHECK

R.L.H. 1 NOV. 55

FORMTEK

DRAWN

74-88

3X 6-32 UNC X (.219)
BINDING HEAD COMBINATION
TERMINAL SCREW AND
CUPWASHER

NOTE
1 - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS
OF .139 MAX. DIA. ON 1.000 ± .002 CENTERS.

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

DIFFERENTIAL TRAVEL ---- .475 MAX.
OVERTRAVEL ----- 1.000 MIN.

ELECTRICAL DATA

CONTACT ARRANGEMENT
S. P. D. T.

L96 15A 125, 250 OR 480 VAC
1/2A 125 VDC, 1/4A 250 VDC
1/8HP 125 VAC, 1/4HP 250 VAC

L288
L299
L306

CE D

SP

16A 250V ~ T85 5E4

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE
SPECIFIED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE	(.0)	±.000
TWO PLACE	(.00)	±.015
THREE PLACE	(.000)	±.005
ANGLES		±

WEIGHT .075 L B.

