



28-Jan-2020

PCN #:E-20-000310

Subject:AMPMODU MTE HEADER ASSEMBLIES

Description of Change: To provide flexibility to our manufacturing processes, we are allowing the manufacturing plants, when possible, to utilize regrind resin, up to the allowable limit specified on the UL Yellow Card, in the molding process. Adding feature at latch to increase mold efficiency.

Reason: Product Improvement. Making a more robust tool to prevent mold down time and increase mold efficiency. Second item is to provide an option of when adequate regrind is generated, Manufacturing can add it to the production. The material is the same formulation as currently used.

Key Dates:

Contact By Date:29-May-2020

Implementation Date:29-May-2020

Product Affected

147969-4

1825573-2

5-147324-7

5-147324-1

1825514-5

147324-1

5-147324-2

1571260-1

6-147324-1

147324-3

1825574-3

5-1825574-4

1825574-2

5-147969-1

Product Affected

5-147324-4

1571796-2

5-147324-6

5-147324-3

1825514-4

5-147324-9

1977162-5

1825533-1

1825533-2

147324-5

147324-4

6-147324-0

The dates on the product change notification (PCN) are best estimate dates determined at the time of issuance. Actual implementation dates may vary from such dates.

The change described in the PCN can be withdrawn, without notice, for any or all of the products identified on the PCN.

TE Connectivity corporate policy is for PCNs to be valid for 60 days and obsolescence notices to be valid for 180 days after date of issue.

For confirmation or additional information on the change, please contact the TE Connectivity Product Information Center at 800-522-6752 or your TE Connectivity Sales Representative.