



Notes 1. Lead co-planarity shall be 0.1mm max
2. Please consult Hirose When the product is monuted to FPC.

3	Brass	Top surface : Sn plating 1μm min Under plating : Cu plating 0.3μm min	6	PS	Reel . Black
2	Brass	Contact area : Au plating 0.05μm min Lead area : Au plating 0.05μm min Under plating : Ni plating 1μm min	5	Polyester	Clear
1	LCP	Black . UL94V-0	4	PS	Clear
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 5 : 1	COUNT 4	DESCRIPTION OF REVISIONS DIS-H-00002928	DESIGNED TS.MIYAKI
APPROVED : KI. AKIYAMA		12.07.02	DRAWING NO. EDC-337114-51-01		
CHECKED : HK. UMEHARA		12.07.02	PART NO. DF50A-12P-1HC(51)		
DESIGNED : ST. SATO		12.06.29	CODE NO. CL665-1041-8-51		
DRAWN : MI. SAKIMURA		12.06.28	1/2		

Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case that the application demands a high level of reliability, such as automotive,
please contact a company representative for further information.

