


RECOMMENDED PC BOARD HOLE PATTERN  
(PCB THICKNESS : t=1.6)



PART NO.	CODE NO.	PIN	A	B
A3B- 4PA-2DSA(51)	CL621-0401-1-51	4	4	2
A3B- 6PA-2DSA(51)	CL621-0402-4-51	6	6	4
A3B- 8PA-2DSA(51)	CL621-0403-7-51	8	8	6
A3B-10PA-2DSA(51)	CL621-0404-0-51	10	10	8
A3B-12PA-2DSA(51)	CL621-0405-2-51	12	12	10
A3B-14PA-2DSA(51)	CL621-0406-5-51	14	14	12
A3B-16PA-2DSA(51)	CL621-0407-8-51	16	16	14
A3B-18PA-2DSA(51)	CL621-0408-0-51	18	18	16
A3B-20PA-2DSA(51)	CL621-0409-3-51	20	20	18
A3B-22PA-2DSA(51)	CL621-0410-2-51	22	22	20
A3B-24PA-2DSA(51)	CL621-0411-5-51	24	24	22
A3B-26PA-2DSA(51)	CL621-0412-8-51	26	26	24
A3B-28PA-2DSA(51)	CL621-0413-0-51	28	28	26
A3B-30PA-2DSA(51)	CL621-0414-3-51	30	30	28
A3B-32PA-2DSA(51)	CL621-0415-6-51	32	32	30
A3B-44PA-2DSA(51)	CL621-0421-9-51	44	44	42
A3B-50PA-2DSA(51)	CL621-0424-7-51	50	50	48

1		POLYAMIDE		BLACK	UL94V-0	2		BRASS		CONTACT AREA : GOLD FLASH	
NO.		MATERIAL		FINISH , REMARKS		NO.		MATERIAL		DIP AREA : TIN-PLATING 2μm	
										UNDER PLATING : NICKEL 2μm	
UNITS mm				SCALE 5 : 1		COUNT 		DESCRIPTION OF REVISIONS		DESIGNED	
										CHECKED	
										DATE	
		HIROSE ELECTRIC CO., LTD.		APPROVED : NH. NAKATA		17. 04. 10		DRAWING NO.		EDC-375929-00-00	
				CHECKED : HT. YAMAGUCHI		17. 04. 10		PART NO.		A3B- * PA-2DSA(51)	
				DESIGNED : HR. NAGAYASU		17. 04. 10		CODE NO.		CL621	
				DRAWN : HR. NAGAYASU		17. 04. 10				1/1	