



Notes 1 : Lead co-planality include reinforced metal fittings shall be 0.1mm MAX.
2 : If there are pattern and a bia hole on part, there is a possibility that it will make contact with the leads.

Part No.	Number of contacts	Code No.	A	B	C	D
DF13E-10DP-1.25V(76)	10	CL536-0566-0-76	12.1	5.0	7.5	8.7
DF13E-20DP-1.25V(76)	20	CL536-0567-0-76	18.35	11.25	13.75	14.95
DF13E-30DP-1.25V(76)	30	CL536-0568-0-76	24.60	17.50	20.00	21.20
DF13E-40DP-1.25V(76)	40	CL536-0569-0-76	30.85	23.75	26.25	27.45

2	Brass	Contact area:Gold plated 0.2μm MIN	5	Elastomer	Gray
		Lead area:Tin-copper plated 1μm MIN	4	R. PVC	Electrostatic protection. Clear
1	Polyamide	Under plating:Nickel 1μm MIN	3	Phosphor bronze	Tin plated 1μm MIN
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 5 : 1	COUNT 	DESCRIPTION OF REVISIONS	
HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA	18. 04. 05	DRAWING NO.	EDC-367983-76-00
		CHECKED : TS. FUKUSHIMA	18. 04. 05	PART NO.	DF13E-*DP-1.25V(76)
		DESIGNED : TS. KUMAZAWA	18. 04. 05	CODE NO.	CL536-
		DRAWN : MK. INOUE	18. 04. 05		

Aug.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case that the application demands a high level of reliability, such as automotive,
please contact a company representative for further information.

