

## 3, 4 and 5-Pin Field Wireable Connectors

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection



| Housing Style          | Female Part Number                             | Male Part Number                                 | Features   | Pinout               |
|------------------------|--|--|--|----------------------|
| <p><b>B 41 ..</b></p>  | <p><b>B 4131-0/9</b><br/><b>B 4231-0/9</b></p> | <p><b>BS 4131-0/9</b><br/><b>BS 4231-0/9</b></p> | <p>Glass filled nylon, PG 9 cable gland, accepts 6-8 mm cable diameter screw terminals, accepts up to 16 AWG conductors, 85°C, 250 V, 12 A, Mates with all 3-pin cordsets and receptacles</p>      | <p><b>Female</b></p> |
| <p><b>B 42 ..</b></p>  | <p><b>B 4131-0/13.5</b></p>                    | <p><b>BS 4131-0/13.5</b></p>                     | <p>Glass filled nylon, PG 13.5 cable gland, accepts 10-12 mm cable diameter screw terminals, accepts up to 16 AWG conductors, 85°C, 250 V, 12 A, Mates with all 3-pin cordsets and receptacles</p> | <p><b>Male</b></p>   |
| <p><b>B 41 ..</b></p>  | <p><b>B 4141-0/9</b><br/><b>B 4241-0/9</b></p> | <p><b>BS 4141-0/9</b><br/><b>BS 4241-0/9</b></p> | <p>Glass filled nylon, PG 9 cable gland, accepts 6-8 mm cable diameter screw terminals, accepts up to 16 AWG conductors 85°C, 250 V, 9 A, Mates with all 4-pin cordsets and receptacles</p>        | <p><b>Female</b></p> |
| <p><b>BS 41 ..</b></p> | <p><b>B 4141-0/13.5</b></p>                    | <p><b>BS 4141-0/13.5</b></p>                     | <p>Glass filled nylon, PG 13.5 cable gland, accepts 10-12 mm cable diameter screw terminals, accepts up to 16 AWG conductors, 85°C, 250 V, 9 A, Mates with all 4-pin cordsets and receptacles</p>  | <p><b>Male</b></p>   |
| <p><b>B 41 ..</b></p>  | <p><b>B 4151-0/9</b><br/><b>B 4251-0/9</b></p> | <p><b>BS 4151-0/9</b><br/><b>BS 4251-0/9</b></p> | <p>Glass filled nylon, PG 9 cable gland, accepts 6-8 mm cable diameter, screw terminals, accepts up to 16 AWG conductors, 85°C, 250 V, 9 A, Mates with all 5-pin cordsets and receptacles</p>      | <p><b>Female</b></p> |
| <p><b>B 42 ..</b></p>  | <p><b>B 4151-0/13.5</b></p>                    | <p><b>BS 4151-0/13.5</b></p>                     | <p>Glass filled nylon, PG 13.5 cable gland, accepts 10-12 mm cable diameter screw terminals, accepts up to 16 AWG conductors, 85°C, 250 V, 9 A</p>   | <p><b>Male</b></p>   |
| <p><b>BS 42 ..</b></p> | <p><b>B 4151-0/16</b></p>                      | <p><b>BS 4151-0/16</b></p>                       | <p>Glass filled nylon, PG 16 cable gland, accepts 12-14 mm cable diameter screw terminals, accepts up to 16 AWG conductors, 85°C, 250 V, 9 A</p>   | <p><b>Male</b></p>   |