



M12 A-coded 4-poles, female angled overmolded connector

Loading-Plan:

- 1 brown
- 2 white
- 3 blue
- 4 black

- Protection level: IP67
- Temperature range: -25°C ... +80°C

length in "1m" step	40	XXX=400
	39	XXX=390
	.	.
	12	XXX=120
	11	XXX=110
length in "0.1m" step	10	XXX=100
	9.9	XXX=099
	9.8	XXX=098
	.	.
	0.4	XXX=004
	0.3	XXX=003
	0.2	XXX=002
	0.1	XXX=001
Step	a [m]	XXX

4.0 to 40	+1%
0.1 to 3.9	+0.04
a [m]	Tolerance

Part no.	213487004XXXXX
----------	----------------

Type of cable	XX
PVC grey, 4x0.34mm²	XX=84
PUR black, 4x0.34mm²	XX=91

All rights reserved
Department EC PD - RO
HARTING Electronics GmbH
D-32339 Espelkamp

All Dimensions in mm
Original Size DIN A3

Scale
2:1

Free size tol.

Created by
TOMUTA

Inspected by
AVRAM

Standardisation
HOFFMANN

Title
M12 A-coded Cable Assembly

Type
TB

Date
2015-06-29

State
Final Release

Doc-Key / ECM-Nr.
100578836/UGD/009/B
500000090069

Rev.
B

Page
1/1