



LM048 Bluetooth® v2.0, v2.1 RS232 Serial Adapter


Standalone (With Embedded Bluetooth® v2.0 / v2.1 Stack)

Product LM048
Part No See Last Page
Revised 16/MAY/2018
Datasheet Version 2.1



New
v3

See version
notes page
for changes



Features

- World's smallest Bluetooth® Serial Adapter (RS232)
- Bluetooth® v2.0, v2.1 wireless technology
- dBm Outputs TBA (expecting as previous version (18 dBm Tx Output Power and -86 dBm Rx Sensitivity)
- Serial (RS232) interface
- Serial Port Profile (SPP) available
- Programmable Standalone Module (With Embedded Bluetooth® v2.0 / v2.1 Stack)
- Unique patented firmware enabling serial printer functionality
- Up to 100m range (in open space)
- 46.3mm x 34mm x 16mm
- Powered by USB - Mini USB, DB9 or AC adaptor
- DTE / DCE (Master / Slave) mode switch
- DTR / DSR Handshaking and RTS / CTS Flow control lines
- Full Duplex for simultaneous communication between sender and receiver
- Ease of configuration and setup using the LM149 software
- Configurations pre-installed on production
- Fully Certified Solution
See our website for this products certifications.
RoHS, REACH and WEEE

Typical Industries

- EPOS
- Aviation
- M2M
- Automotive
- LNG

Overview

The LM048 is the world's smallest Bluetooth® serial adapter (RS232), providing a secure and reliable Bluetooth® v2.0, v2.1 connection.

This wireless connection reaches a range of up to 100m in open space, replacing RS232 cables between a master (DTE) device and slave (DCE) devices such as printers, data loggers and digital signalling devices.

The LM048 patented firmware allows the serial configurations to be used. The firmware controls the RS232 signals, including DTR / DSR handshaking and RTS / CTS flow control lines. The LM048 is powered by USB - Mini USB, DB9 or AC adaptor and all settings and configurations are even retained when the adapter is powered down.

Our LM149 software is used to change the settings and configurations; including the auto connect function, discoverable / non-discoverable function, device name, baud rate, data bits and flow control. The AT Command set is used to change the configurations, plus the developer can also configure and modify the settings of a remote LM048 from a local LM048. Customised configurations and settings can be preloaded to the LM048, simplifying the manufacturing and testing process.



LM048 Bluetooth® v2.0, v2.1 RS232 Serial Adapter

Standalone (With Embedded Bluetooth® v2.0 / v2.1 Stack)

Product

LM048

Part No

See Last Page

General Specification

Wireless

Bluetooth® Standard	v2.0 and v2.1 wireless technology
Adapter Type	Standalone (Configurable with AT Commands)
Profiles	SPP

Hardware

Chipset	CSR
Antenna	IC Antenna Onboard
Flash Memory	8 Mbit
RAM	48 KB
Interfaces	Serial (RS232)
Power Supply	4V to 12V DC
Crystal Oscillator	16 MHz
LED Indicators	Link (BLUE), Data (ORANGE) and Power (RED)

RS232 (Serial)

RS232 Interface	D_SUB 9 pin female
Signal	RxD, TxD, DTR, DSR, RTS, CTS and GND
Full Duplex	Yes
Baud Rate	1.2, 2.4, 4.8, 9.6, 19.2, 38.4, 57.6, 115.2, 230.4, 460.8 and 921.6 Kbps

RF Characteristics

Tx Output Power	18 dBm (Maximum)
Rx Sensitivity	-86 dBm (Typical)
Antenna Gain	1 dBi to 2 dBi (Maximum)
Current Consumption	90 mA (Typical)
Range (in open space)	Up to 100m
Data Rate	Up to 3Mbps
Frequency	2.4 GHz to 2.485 GHz
Hopping	1,600/sec, 1MHz channel space
Modulation Scheme	GFSK-Mbps, DQPSK-2 Mbps, and 8-DPSK-3Mbps

Physical Characteristics

Operating Temperature	-10°C to +70°C
Dimensions (L x W x H)	46.3mm x 34mm x 16mm
Weight	20.19g +/- 0.25g tolerance
Certifications	See our website for this products certifications.
Compliance	RoHS, REACH and WEEE




LM048 Bluetooth® v2.0, v2.1 RS232 Serial Adapter

Standalone (With Embedded Bluetooth® v2.0 / v2.1 Stack)

Product
Part No

LM048
See Last Page

Signals



Female DB9



Pin out for LM048 Adapter

Pin	RS232 Signal	DTE to DCE Direction	DCE to DTE Direction	Description
1	CD	Input	Output	Not Connected
2	RxD	Input	Output	Receive Data
3	TxD	Output	Input	Transmit Data
4	DTR	Output	Input	Data Terminal Ready
5	GND	n/a	n/a	Signal Ground
6	DSR	Input	Output	Data Set Ready
7	RTS	Output	Input	Request to Send
8	CTS	Input	Output	Clear to Send
9	Vcc	Input	Input	Power Supply

Factory Settings

The factory settings of the COM Port are as follows:

Baud Rate	19200 bps
Data Bits	8
Parity	None
Stop Bits	1
Flow Control	None

Customised settings are available as factory settings upon special request; Bonding, Pre-Pairing, different Baud Rates, Data Bits, Parity and Flow Control Settings.

LM048 Bluetooth® v2.0, v2.1 RS232 Serial Adapter


Standalone (With Embedded Bluetooth® v2.0 / v2.1 Stack)

Product
Part No

LM048
See Last Page

Hardware Structure

- 1 Link LED.
- 2 Data LED.
- 3 Power LED.
- 4 Mini USB Connector.
- 5 RS232 Connector.
- 6 Slide Switch.
- 7 Reset Button.



Switch Functions

Reset Button


By pressing the Reset Button you can:

Disconnect a wireless connection (after a short press).
Restore the factory settings (after over 3 seconds press).

Slide Switch

The slide switch can swap TxD / RxD, RTS / CTS and DTR / DSR Signals.
By switching, you can set the adapter as a DTE (towards antenna connector)
or a DCE (towards RS232 connector).

Physical Dimensions





LM048 Bluetooth® v2.0, v2.1 RS232 Serial Adapter
Standalone (With Embedded Bluetooth® v2.0 / v2.1 Stack)

Product LM048
Part No See Last Page

Datasheet Version Notes

v1.0	13 MAR 2018	Added version notes to datasheet.
v1.1	1 MAY 2018	Existing Part Numbers end of life (due to hardware change).
v2.0	1 MAY 2018	New LM048 version 3 release (with new power amplifier replacing previous.
v2.1	16 MAY 2018	New Part Numbers released for LM048 version 3.





LM048 Bluetooth® v2.0, v2.1 RS232 Serial Adapter

Standalone (With Embedded Bluetooth® v2.0 / v2.1 Stack)

Product
Part No

LM048
See Below

LM048 Packaging Options



048-3000

Previously 048-0000

AO - Adapter Only

1 x Bluetooth® Serial Adapter



048-3006

Previously 048-0006

SRP - Single Retail Pack

1 x Bluetooth® Serial Adapter
1 x DB9 male to female connector
1 x USB - mini USB Cable for power supply
1 x All in one power supply (UK, EU and US)

Optional

LM025 Slim Line 9 pin to 25 pin Convertor



048-3011

Previously 048-0011

Twin Pack Pre-Paired

2 x Bluetooth® Serial Adapter



048-3012

Previously 048-0012

TRP - Twin Retail Pack

2 x Bluetooth® Serial Adapters
1 x DB9 male to female connector
1 x USB mini USB Cable for power supply
1 x All in one power supply (UK, EU and US)

Optional

LM025 Slim Line 9 pin to 25 pin Convertor

• See our website to download any applicable Product Software, Manuals and Notes - <http://www.lm-technologies.com/downloads>